

PRODUCT DATA SHEET
HydroStrip
HS-300PW



A Highly Adhesive Water-Based Surface Primer for Concrete, Plastic and Metal Surfaces



PHYSICAL PROPERTIES OF WATER-BASED ADHESIVE SURFACE PRIMER	
Description	HS-300PW
Color:	Bright Orange
% Solids:	33% minimum
Solvent Type:	Water
Flash Point:	200°F minimum
Weight / Gallon:	8.0 Pounds
Dry Time @ 77°F (25°C):	10 minutes
Dry Time @ 40°F (4°C):	60 minutes
Clean Up:	Soap and Water
Coverage Per Gallon:	Approx. 400 sq ft on wet cast concrete. Coverage diminishes on dry cast concrete.
Appropriate Substrates:	Concrete, Plastic, Metal
Min. Storage Temperature:	40°F (4°C) Product should not be allowed to freeze
Min. Application Temperature:	40°F (4°C)
Surface When Dry:	Tacky

Where to use HydroStrip

Water-Based Adhesive Surface Primer

For use on concrete, plastic and metal surfaces, HydroStrip HS-300PW enhances the bonding between preformed sealants and concrete surfaces aiding in the installation process. Conveniently applied at the job site, HS-300PW improves adhesion of the sealant to the concrete.

Limited Warranty

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufactures in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the **users' responsibility** to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

141 Hammond Street
 Carrollton, GA 30117
 Phone 770-832-2000 • 800-862-4835 • FAX 770-832-2095
 Visit our website @ www.bometals.com
 Address email to info@bometals.com
Founded in 1989, BoMetals has become an industry leader in the design and manufacture of concrete and masonry accessories.